

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

*** 1 Identification**

- **Product Identifier**
- **Trade Name:** AcriFluor Decolorizer
- **Product Number:** 384
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description:** Industry-specific application
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
Scientific Device Laboratory
411 Jarvis Avenue
Des Plaines, IL 60018
847-803-9495
- **Emergency telephone number:**
For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
Within USA and Canada: 1-800-424-9300 or Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

*** 2 Hazard(s) Identification**

- **Classification of the substance or mixture:**



Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger
- **Hazard-determining components of labeling:**
Ethanol
Sulfuric acid
- **Hazard statements:**
H225 Highly flammable liquid and vapor.
H315+H320 Causes skin and eye irritation.
H335 May cause respiratory irritation.
- **Precautionary statements:**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

Trade Name: AcriFluor Decolorizer

- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 If on skin: Wash with plenty of water.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a poison center/doctor if you feel unwell.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

0 % of the mixture consists of component(s) of unknown toxicity.

Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

NFPA ratings (scale 0 - 4)

 Health = 1
 Fire = 3
 Reactivity = 0

HMIS-ratings (scale 0 - 4)

 Health = 1
 Fire = 3
 Physical Hazard = 0

Hazard(s) not otherwise classified (HNOC): None known

* 3 Composition/Information on Ingredients

Chemical characterization: Mixtures
Description: Mixture of substances listed below with non-hazardous additions.

Dangerous Components:

CAS: 64-17-5	Ethanol
RTECS: KQ 6300000	Flam. Liq. 2, H225; Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320
CAS: 7664-93-9	Sulfuric acid
	Skin Corr. 1A, H314

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

* 4 First-Aid Measures

Description of first aid measures
After inhalation: In case of unconsciousness place patient stably in the side position for transportation.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

Trade Name: AcriFluor Decolorizer

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

- **After eye contact:**

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

- **After swallowing:** If swallowed and symptoms occur, consult a doctor.

- **Information for doctor**

- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

* 5 Fire-Fighting Measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** No further relevant information.

- **Special hazards arising from the substance or mixture:** No further relevant information available.

- **Advice for firefighters**

- **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

* 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** Dilute with plenty of water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

· PAC-1:		
64-17-5	Ethanol	1,800 ppm
7664-93-9	Sulfuric acid	0.20 mg/m ³
· PAC-2:		
64-17-5	Ethanol	3300* ppm
7664-93-9	Sulfuric acid	8.7 mg/m ³
· PAC-3:		
64-17-5	Ethanol	15000* ppm
7664-93-9	Sulfuric acid	160 mg/m ³

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

Trade Name: AcriFluor Decolorizer

* 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect from heat.
 Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
 Store in the original container.
 Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
 Protect from heat and direct sunlight.
- **Specific end use(s):** No further relevant information available.

* 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**

- **Components with occupational exposure limits:**

64-17-5 Ethanol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm

7664-93-9 Sulfuric acid

PEL	Long-term value: 1 mg/m ³
REL	Long-term value: 1 mg/m ³
TLV	Long-term value: 0.2* mg/m ³ *as thoracic fraction

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**
- **Personal protective equipment**
- **General protective and hygienic measures:**
 The usual precautionary measures for handling chemicals should be followed.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing and wash before reuse.
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

Trade Name: AcriFluor Decolorizer
Protection of hands:


Protective gloves

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection:


Tightly sealed goggles

Limitation and supervision of exposure into the environment: None

* 9 Physical and Chemical Properties

Information on basic physical and chemical properties
General Information
Appearance:
Form:

Liquid

Color:

Dark blue

Odor:

Odorless

Odor threshold:

Not determined.

pH-value @ 20 °C (68 °F):

1.5

Change in condition
Melting point/Melting range:

Not determined.

Boiling point/Boiling range:

≥78 °C (≥172.4 °F)

Flash point:

≥13 °C (≥55.4 °F)

Flammability (solid, gaseous):

Not applicable.

Ignition temperature:

≥425 °C (≥797 °F)

Decomposition temperature:

Not determined.

Auto igniting:

Product is not self-igniting.

Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

Explosion limits:
Lower:

0 Vol %

Upper:

15 Vol %

Vapor pressure @ 20 °C (68 °F):

≤59 hPa (≤44.3 mm Hg)

Density:

Not determined.

Relative density:

Not determined.

Vapor density:

Not determined.

Evaporation rate:

Not determined.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

Trade Name: AcriFluor Decolorizer

- **Solubility in / Miscibility with:**
- Water:** Fully miscible.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
- Dynamic:** Not determined.
- Kinematic:** Not determined.
- **Solvent content:**
- Organic solvents:** 26.0 %
- Water:** 72.9 %
- VOC content:** 26.00 %
- Solids content:** 0.1 %
- **Other information:** No further relevant information available.

*10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** Heat, flame and ignition sources.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

 · **LD/LC50 values that are relevant for classification:**

64-17-5 Ethanol		
Oral	LD50	7,060 mg/kg (Rat) Remarks: Lungs, Thorax, or Respiration: Other changes. Carcinogenicity - Mouse - Oral Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors. Blood: Lymphomas including Hodgkin's disease. Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Heart - Irregularities - Based on Human Evidence Central nervous system - Breathing difficulties - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence
Inhalative	LC50/4 h LC50/96 hours	20,000 mg/l (Rat) 12,900-15,300 mg/l (Trout)
7664-93-9 Sulfuric acid		
Oral	LD50 Oral	2,140 ml/kg (Rat)
Inhalative	LC50/96 hours	375 mg/l (Rat) Sulfuric acid is harmful by all routes of entry.

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Irritating effect.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

Trade Name: AcriFluor Decolorizer
Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
 Irritant

Carcinogenic categories:
IARC (International Agency for Research on Cancer):

- Group 1 - Carcinogenic to humans
- Group 2A - Probably carcinogenic to humans
- Group 2B - Possibly carcinogenic to humans
- Group 3 - Not classifiable as to its carcinogenicity to humans
- Group 4 - Probably not carcinogenic to humans

The IARC (the International Agency for Research on Cancer) concluded that ethanol found alcoholic beverages to be Group 1 - Carcinogenic to humans. All other instances it is not consider carcinogenic.

64-17-5	Ethanol	1
7664-93-9	Sulfuric acid	7664-93-9
314-13-6	Evans Blue	3

NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

*12 Ecological Information

Toxicity:
Aquatic toxicity:
64-17-5 Ethanol

EC50 34,900 mg/l (Daphnia)

7664-93-9 Sulfuric acid

EC50 22 mg/l (Daphnia)

Persistence and degradability: No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Additional ecological information:

General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No further relevant information available.

*13 Disposal Considerations

Waste treatment methods

Recommendation: Observe all federal, state and local environmental regulations when disposing of this material.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

Trade Name: AcriFluor Decolorizer

 · **Recommended cleansing agent:** Water, if necessary with cleansing agents.

*14 Transport Information

- **UN-Number:**
- **DOT** NA1993
- **ADR/ADN, IMDG, IATA** UN1993
- **UN proper shipping name:**
- **DOT** Flammable liquids, n.o.s. (Ethanol)
- **ADR/ADN** UN1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL))
- **IMDG** FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL))
- **IATA** FLAMMABLE LIQUID, N.O.S. (ETHANOL)
- **Transport hazard class(es):**
- **DOT**



- **Class:** 3 Flammable liquids
- **Label:** 3

 · **ADR/ADN**


- **Class:** 3 (F1) Flammable liquids
- **Label:** 3

 · **IMDG, IATA**


- **Class:** 3 Flammable liquids
- **Label:** 3
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** I
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Warning: Flammable liquids
- **Hazard identification number (Kemler code):** 33
- **EMS Number:** F-E,S-E
- **Stowage Category** E
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations:** On passenger aircraft/rail: 1 L
On cargo aircraft only: 30 L
- **Remarks:** ERG Guide Number: 128

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

Trade Name: AcriFluor Decolorizer
· ADR/ADN
· Excepted quantities (EQ):

Code: E3

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 300 ml

· IMDG
· Limited quantities (LQ):

0

· Excepted quantities (EQ):

Code: E3

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 300 ml

· UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL)), 3, I

*15 Regulatory Information

· Safety, health and environmental regulations/legislation specific for the substance or mixture:
· SARA (Superfund Amendments and Reauthorization):
· Section 355 (extremely hazardous substances):

7664-93-9	Sulfuric acid
-----------	---------------

· Section 313 (Specific toxic chemical listings):

7664-93-9	Sulfuric acid
-----------	---------------

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients are listed.

· California Proposition 65:


WARNING: This product can expose you to chemicals including the listed chemicals which are known to the State of California to cause cancer, birth defects and/or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

64-17-5	Ethanol
---------	---------

· New Jersey Right-to-Know List:

64-17-5	Ethanol
---------	---------

7664-93-9	Sulfuric acid
-----------	---------------

· New Jersey Special Hazardous Substance List:

64-17-5	Ethanol		CA, MU, TE, F3
---------	---------	--	----------------

7664-93-9	Sulfuric acid		CA, CO, R2
-----------	---------------	--	------------

· Pennsylvania Right-to-Know List:

64-17-5	Ethanol
---------	---------

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

Trade Name: AcriFluor Decolorizer

7664-93-9	Sulfuric acid
-----------	---------------

· Pennsylvania Special Hazardous Substance List:

7664-93-9	Sulfuric acid	E
-----------	---------------	---

· Carcinogenic categories:
· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):

64-17-5	Ethanol	A3
7664-93-9	Sulfuric acid	A2

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:

· Signal word: Danger

· Hazard-determining components of labeling:

 Ethanol
 Sulfuric acid

· Hazard statements:

 H225 Highly flammable liquid and vapor.
 H315+H320 Causes skin and eye irritation.
 H335 May cause respiratory irritation.

· Precautionary statements:

 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
 P264 Wash thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 If on skin: Wash with plenty of water.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a poison center/doctor if you feel unwell.
 P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/06/2020

Reviewed on 03/06/2020

Trade Name: AcriFluor Decolorizer

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of last revision/ revision number: 03/06/2020 / 3**· Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * Data compared to the previous version altered.SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106